



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 26

LOCTITE ABLESTIK CE 3104WXL known as CE 3104 WXL 25 G

SDS No. : 373840

V005.0

Revision: 12.03.2025

printing date: 02.07.2025

Replaces version from: 24.07.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE ABLESTIK CE 3104WXL known as CE 3104 WXL 25 G

UFI: P02E-MXVE-320X-76E9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ireland

Operations and Research Limited

Tallaght Business Park, Whitestown

24 Dublin

Ireland

Phone: +353 (0353) 1 404 6444

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

00353 14046280

National Poisons Information Centre: Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week)

Healthcare Professionals: +353 (1) 809 2566 (24-hour service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation	Category 2
H315 Causes skin irritation.	
Serious eye irritation	Category 2
H319 Causes serious eye irritation.	
Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Germ cell mutagenicity	Category 2
H341 Suspected of causing genetic defects.	
Toxic to reproduction	Category 1B
H360Df May damage the unborn child. Suspected of damaging fertility.	
Specific target organ toxicity - repeated exposure	Category 2
H373 May cause damage to organs through prolonged or repeated exposure.	
Acute hazards to the aquatic environment	Category 1
H400 Very toxic to aquatic life.	
Chronic hazards to the aquatic environment	Category 1
H410 Very toxic to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains

Silver $\geq 99,9$ % Ag in powder ($>100\text{nm}<1\text{mm}$)

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane
Bisphenol-F epichlorhydrin resin; MW<700
8-Hydroxyquinoline
Epoxy resin-amine condensate
Neodecanoic acid, oxiranylmethyl ester

Signal word:

Danger

Hazard statement:

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H341 Suspected of causing genetic defects.
H360Df May damage the unborn child. Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

Supplemental information

Restricted to professional users.

Precautionary statement: Prevention

P201 Obtain special instructions before use.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing.

Precautionary statement: Response

P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration $\geq$ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

4,4'-Isopropylidenediphenol 80-05-7	ED
--	----

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Silver $\geq 99,9\%$ Ag in powder ($>100\text{nm}<1\text{mm}$) 7440-22-4 231-131-3 01-2119555669-21	50- < 100 %	Repr. 2, H361f STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 10 M chronic = 10	EU OEL
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3 216-823-5 01-2119456619-26	5- < 10 %	Eye Irrit. 2, H319 Aquatic Chronic 2, H411 Skin Sens. 1, H317 Skin Irrit. 2, H315	Eye Irrit. 2; H319; C $\geq 5\%$ Skin Irrit. 2; H315; C $\geq 5\%$	
Bisphenol-F epichlorhydrin resin; MW<700 ----- 500-006-8 01-2119454392-40	5- < 10 %	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411		
8-Hydroxyquinoline 148-24-3 205-711-1	1- < 3 %	Repr. 1B, H360D Acute Tox. 3, Oral, H301 Aquatic Acute 1, H400 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 1, H410	M acute = 1 M chronic = 1	
Epoxy resin-amine condensate 68002-42-6 500-181-0 01-2119967768-13	1- < 3 %	Skin Sens. 1B, H317		
Neodecanoic acid, oxiranylmethyl ester 26761-45-5 247-979-2 01-2119431597-33	1- < 3 %	Aquatic Chronic 2, H411 Skin Sens. 1A, H317 Muta. 2, H341 Repr. 2, H361d	Skin Sens. 1A; H317; C $\geq 0,001\%$	
4,4'-Isopropylidenediphenol 80-05-7 201-245-8 01-2119457856-23	0,01- < 0,1 %	Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 Repr. 1B, H360F Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 1 M chronic = 10 ===== oral:ATE = 2.500 mg/kg	SVHC ED EU OEL

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

SKIN: Redness, inflammation.

EYE: Irritation, conjunctivitis.

Prolonged or repeated skin contact with silver and its salts may cause a blue-gray discoloration of the skin and mucous membranes that is irreversible (Argyria).

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Avoid dust formation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

Scrape up as much material as possible.

Sweep up spilled material. Avoid creating dust.

Store in a partly filled, closed container until disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage
--

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Keep container tightly sealed.

Refer to Technical Data Sheet.

7.3. Specific end use(s)

Epoxy adhesive

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silver 7440-22-4 [Silver, metallic]		0,1	Time Weighted Average (TWA):	Indicative	ECTLV
Silver 7440-22-4 [Silver (metallic)]		0,1	Time Weighted Average (TWA):	Indicative OELV	IR_OEL
4,4'-Isopropylidenediphenol 80-05-7 [Bisphenol A (4,4'-isopropylidenediphenol)]		2	Time Weighted Average (TWA):	Binding OELV	IR_OEL
4,4'-Isopropylidenediphenol 80-05-7 [Bisphenol A; 4,4'-Isopropylidenediphenol]		2	Time Weighted Average (TWA):		EU OELIII
4,4'-Isopropylidenediphenol 80-05-7 [Bisphenol A (4,4'-Isopropylidenediphenol) (Inhalable fraction)]		2	Time Weighted Average (TWA):	Indicative	ECTLV

Occupational Exposure LimitsValid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4 [SILVER (METALLIC)]		0,1	Time Weighted Average (TWA):		EH40 WEL
4,4'-Isopropylidenediphenol 80-05-7 [BISPHENOL A]		2	Time Weighted Average (TWA):		EH40 WEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	aqua (freshwater)		0,00004 mg/l				
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	aqua (marine water)		0,00086 mg/l				
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	sewage treatment plant (STP)		0,025 mg/l				
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	sediment (freshwater)				438,13 mg/kg		
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	sediment (marine water)				438,13 mg/kg		
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Air						no hazard identified
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Soil				1,41 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	aqua (freshwater)		0,006 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	Freshwater - intermittent		0,018 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	aqua (marine water)		0,001 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	Marine water - intermittent		0,002 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	sewage treatment plant (STP)		10 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	sediment (freshwater)				0,341 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	sediment (marine water)				0,034 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	Soil				0,065 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3- epoxypropane, number average molecular weight ≤ 700 1675-54-3	oral				11 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric	Air						no hazard identified

reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3							
Reaction mass bisphenol-F-(epichlorhydrin) -----	aqua (freshwater)		0,003 mg/l				
Reaction mass bisphenol-F-(epichlorhydrin) -----	aqua (marine water)		0,0003 mg/l				
Reaction mass bisphenol-F-(epichlorhydrin) -----	sewage treatment plant (STP)		10 mg/l				
Reaction mass bisphenol-F-(epichlorhydrin) -----	sediment (freshwater)				0,294 mg/kg		
Reaction mass bisphenol-F-(epichlorhydrin) -----	sediment (marine water)				0,0294 mg/kg		
Reaction mass bisphenol-F-(epichlorhydrin) -----	Soil				0,237 mg/kg		
Reaction mass bisphenol-F-(epichlorhydrin) -----	aqua (intermittent releases)		0,0254 mg/l				
Reaction mass bisphenol-F-(epichlorhydrin) -----	Air						no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin) -----	Predator						no potential for bioaccumulation
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 2-methylimidazole 68002-42-6	aqua (freshwater)		0,1 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 2-methylimidazole 68002-42-6	aqua (marine water)		0,01 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 2-methylimidazole 68002-42-6	sediment (freshwater)				0,38 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 2-methylimidazole 68002-42-6	sewage treatment plant (STP)		10 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 2-methylimidazole 68002-42-6	sediment (marine water)				0,038 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 2-methylimidazole 68002-42-6	Soil				0,018 mg/kg		
2,3-Epoxypropyl neodecanoate 26761-45-5	aqua (freshwater)		0,0035 mg/l				
2,3-Epoxypropyl neodecanoate 26761-45-5	aqua (marine water)		0,00035 mg/l				
2,3-Epoxypropyl neodecanoate 26761-45-5	sewage treatment plant (STP)		50 mg/l				
2,3-Epoxypropyl neodecanoate 26761-45-5	aqua (intermittent releases)		0,035 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	aqua (freshwater)		0,023 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	aqua (marine water)		0,019 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	Freshwater - intermittent		0,011 mg/l				
4,4'-Isopropylidenediphenol 80-05-7	sewage treatment plant (STP)		320 mg/l				

4,4'-Isopropylidenediphenol 80-05-7	sediment (freshwater)				1,2 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	sediment (marine water)				0,24 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	Soil				3,7 mg/kg		
4,4'-Isopropylidenediphenol 80-05-7	Air						no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Predator						no potential for bioaccumulation

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	Workers	inhalation	Long term exposure - systemic effects		0,1 mg/m3	no hazard identified
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	General population	inhalation	Long term exposure - systemic effects		0,04 mg/m3	no hazard identified
Silver >= 99,9 % Ag as powder (>100nm<1mm) classified for environment 7440-22-4	General population	oral	Long term exposure - systemic effects		1,2 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Long term exposure - systemic effects		4,93 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Long term exposure - systemic effects		0,75 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	inhalation	Long term exposure - systemic effects		0,87 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	dermal	Long term exposure - systemic effects		0,0893 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Acute/short term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Acute/short term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	inhalation	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	inhalation	Acute/short term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	dermal	Long term exposure - local effects			no hazard identified

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	dermal	Acute/short term exposure - local effects			no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin) -----	Workers	Inhalation	Long term exposure - systemic effects		29,39 mg/m3	no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin) -----	Workers	dermal	Long term exposure - systemic effects		104,15 mg/kg	no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin) -----	Workers	dermal	Acute/short term exposure - local effects		0,0083 mg/cm2	no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin) -----	General population	Inhalation	Long term exposure - systemic effects		8,7 mg/m3	no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin) -----	General population	dermal	Long term exposure - systemic effects		62,5 mg/kg	no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin) -----	General population	oral	Long term exposure - systemic effects		6,25 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 2-methylimidazole 68002-42-6	Workers	inhalation	Long term exposure - systemic effects		4,93 mg/m3	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 2-methylimidazole 68002-42-6	Workers	dermal	Long term exposure - systemic effects		1,4 mg/kg	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 2-methylimidazole 68002-42-6	General population	inhalation	Long term exposure - systemic effects		0,74 mg/m3	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 2-methylimidazole 68002-42-6	General population	dermal	Long term exposure - systemic effects		0,5 mg/kg	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 2-methylimidazole 68002-42-6	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	
2,3-Epoxypropyl neodecanoate 26761-45-5	Workers	dermal	Long term exposure - systemic effects		4,2 mg/kg	
2,3-Epoxypropyl neodecanoate 26761-45-5	Workers	Inhalation	Long term exposure - systemic effects		5,88 mg/m3	
2,3-Epoxypropyl neodecanoate 26761-45-5	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg	
2,3-Epoxypropyl neodecanoate 26761-45-5	General population	Inhalation	Long term exposure - systemic effects		4 mg/m3	
2,3-Epoxypropyl neodecanoate 26761-45-5	Workers	dermal	Acute/short term exposure - systemic effects			
2,3-Epoxypropyl neodecanoate 26761-45-5	Workers	dermal	Long term exposure - local effects			
2,3-Epoxypropyl neodecanoate 26761-45-5	Workers	dermal	Acute/short term exposure - local effects			
2,3-Epoxypropyl neodecanoate 26761-45-5	General population	dermal	Long term exposure - local effects			
2,3-Epoxypropyl neodecanoate 26761-45-5	General population	dermal	Acute/short term exposure - local			

			effects			
2,3-Epoxypropyl neodecanoate 26761-45-5	General population	oral	Long term exposure - systemic effects		2,5 mg/kg	
4,4'-Isopropylidenediphenol 80-05-7	Workers	dermal	Acute/short term exposure - systemic effects		0,031 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	dermal	Long term exposure - systemic effects		0,031 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	Inhalation	Acute/short term exposure - systemic effects		2 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	Inhalation	Long term exposure - systemic effects		2 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	dermal	Long term exposure - systemic effects		0,002 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	Inhalation	Long term exposure - systemic effects		1 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	inhalation	Long term exposure - local effects		2 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	Workers	inhalation	Acute/short term exposure - local effects		2 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Acute/short term exposure - systemic effects		1 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Long term exposure - local effects		1 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	inhalation	Acute/short term exposure - local effects		1 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	dermal	Acute/short term exposure - systemic effects		0,002 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	oral	Long term exposure - systemic effects		0,004 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol 80-05-7	General population	oral	Acute/short term exposure - systemic effects		0,004 mg/kg	no hazard identified

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	paste
Colour	Silver
Odor	Epoxy
Physical state	solid
Melting point	20 - 25 °C (68 - 77 °F)
Solidification temperature	Not applicable, Product is a solid
Initial boiling point	Not applicable, Polymerizes before boiling point is reached.
Flammability	Not flammable.
Explosive limits	Not applicable, Product is a solid
Flash point	> 96 °C (> 204.8 °F)
Auto-ignition temperature	Not applicable, Product is a solid
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic)	Not applicable, Product is a solid
Viscosity, dynamic	Not available.
()	
Solubility (qualitative)	Insoluble
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	< 0,01 mm hg
(20 °C (68 °F))	
Density	3 g/cm3 None
(25 °C (77 °F))	
Relative vapour density:	Not applicable, Product is a solid
Particle characteristics	Not applicable, mixture is a paste.

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity**10.1. Reactivity**

Reacts with strong oxidants.
Reaction with strong acids.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
Bisphenol-F epichlorhydrin resin; MW<700 -----	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
8-Hydroxyquinoline 148-24-3	LD50	177 mg/kg	mouse	not specified
Epoxy resin-amine condensate 68002-42-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
4,4'- Isopropylidenediphenol 80-05-7	LD50	> 2.000 - < 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
4,4'- Isopropylidenediphenol 80-05-7	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Bisphenol-F epichlorhydrin resin; MW<700 -----	LD50	> 2.000 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
8-Hydroxyquinoline 148-24-3	LD50	> 10.000 mg/kg	rat	not specified
Epoxy resin-amine condensate 68002-42-6	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
4,4'-Isopropylidenediphenol 80-05-7	LD50	3.000 mg/kg	rabbit	not specified

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	irritating			Weight of evidence
Bisphenol-F epichlorhydrin resin; MW<700 -----	irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	irritating			Weight of evidence
Bisphenol-F epichlorhydrin resin; MW<700 -----	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Bisphenol-F epichlorhydrin resin; MW<700 -----	Sub-Category 1A (sensitising)	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	Sub-Category 1A (sensitising)	Guinea pig maximisation test	guinea pig	Magnusson and Kligman Method
4,4'- Isopropylidenediphenol 80-05-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
Bisphenol-F epichlorhydrin resin; MW<700 -----	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	negative	yeast cytogenetic assay	with and without		OECD Guideline 481 (Genetic Toxicology: Saccharomyces cerevisiae, Mitotic Recombination Assay)
4,4'- Isopropylidenediphenol 80-05-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		not specified
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	negative	oral: gavage		mouse	not specified
Bisphenol-F epichlorhydrin resin; MW<700 -----	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	positive	oral: gavage		mouse	OECD Guideline 488 (In Vivo Transgenic Cell Gene Mutation Assays)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	not carcinogenic	dermal	2 y daily	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	not carcinogenic	oral: gavage	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	NOAEL P >= 50 mg/kg NOAEL F1 >= 750 mg/kg NOAEL F2 >= 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Bisphenol-F epichlorhydrin resin; MW<700 -----	NOAEL P > 750 mg/kg NOAEL F1 750 mg/kg NOAEL F2 750 mg/kg	two- generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
4,4'- Isopropylidenediphenol 80-05-7	NOAEL P 300 ppm		oral; feed	mouse	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	NOAEL 50 mg/kg	oral: gavage	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Bisphenol-F epichlorhydrin resin; MW<700 -----	NOAEL 250 mg/kg	oral: gavage	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information**General ecological information:**

Do not empty into drains / surface water / ground water.

12.1. Toxicity**Toxicity (Fish):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	LC50	0,0012 mg/l	96 h	Pimephales promelas	other guideline:
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	EC10	0,00019 mg/l	217 d	Salmo trutta	OECD Guideline 210 (fish early lite stage toxicity test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	LC50	1,75 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	LC50	5,7 mg/l	96 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
8-Hydroxyquinoline 148-24-3	LC50	2 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
8-Hydroxyquinoline 148-24-3	NOEC	0,01001 mg/l	28 d	Oncorhynchus mykiss	OECD Guideline 210 (fish early lite stage toxicity test)
Epoxy resin-amine condensate 68002-42-6	LC50	> 160 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	LC50	9,61 mg/l	96 h	Oncorhynchus mykiss	EPA OTS 797.1400 (Fish Acute Toxicity Test)
4,4'-Isopropylidenediphenol 80-05-7	LC50	4,6 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
4,4'-Isopropylidenediphenol 80-05-7	LOEC	0,000372 mg/l	300 d	Danio rerio	OECD Guideline 234 (Fish Sexual Development Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	EC50	0,00022 mg/l	48 h	Daphnia magna	other guideline:
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	EC50	1,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	EC50	2,55 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
8-Hydroxyquinoline 148-24-3	EC50	3,67 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Epoxy resin-amine condensate 68002-42-6	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Neodecanoic acid,	EC50	4,8 mg/l	48 h	Daphnia magna	OECD Guideline 202

oxiranylmethyl ester 26761-45-5					(Daphnia sp. Acute Immobilisation Test)
4,4'-Isopropylidenediphenol 80-05-7	EC50	0,885 mg/l	48 h	Acartia clausi	other guideline:

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	NOEC	0,00032 mg/l	21 d	Daphnia magna	EPA OPPTS 850.1300 (Daphnid Chronic Toxicity Test)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]biso xirane 1675-54-3	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
8-Hydroxyquinoline 148-24-3	NOEC	0,039 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
4,4'-Isopropylidenediphenol 80-05-7	LOEC	0,00025 mg/l	150 d	Marisa cornuarietis	other guideline:

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	EC10	0,00016 mg/l	15 d	other:	other guideline:
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	EC50	1,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
8-Hydroxyquinoline 148-24-3	EC50	0,71 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
8-Hydroxyquinoline 148-24-3	EC10	0,27 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Epoxy resin-amine condensate 68002-42-6	EC50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	NOEC	1 mg/l	96 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	EC50	2,9 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC50	3,73 mg/l	96 h	other:	OECD Guideline 201 (Alga, Growth Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC10	2,1 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
Bisphenol-F epichlorhydrin resin; MW<700 -----	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	EC50	> 100 mg/l			OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
4,4'-Isopropylidenediphenol 80-05-7	EC10	> 320 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
8-Hydroxyquinoline 148-24-3	not readily biodegradable.	aerobic	6,6 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	under test conditions no biodegradation observed	aerobic	7 - 8 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
4,4'-Isopropylidenediphenol 80-05-7	readily biodegradable	aerobic	89 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	70	42 d	20 °C	Cyprinus carpio	other guideline:
8-Hydroxyquinoline 148-24-3	< 4,2			Cyprinus carpio	OECD Guideline 305 (Bioconcentration: Flow-through Fish Test)
4,4'-Isopropylidenediphenol 80-05-7	5,1 - 67	42 d	25 °C	Cyprinus carpio	other guideline:

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	3,242	25 °C	EU Method A.8 (Partition Coefficient)
Bisphenol-F epichlorhydrin resin; MW<700 -----	2,7 - 3,6		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
8-Hydroxyquinoline 148-24-3	1,66		QSAR (Quantitative Structure Activity Relationship)
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	4,4	20 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
4,4'-Isopropylidenediphenol 80-05-7	3,4	21,5 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Silver >= 99,9 % Ag in powder (>100nm<1mm) 7440-22-4	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Bisphenol-F epichlorhydrin resin; MW<700 -----	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Epoxy resin-amine condensate 68002-42-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Neodecanoic acid, oxiranylmethyl ester 26761-45-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
4,4'-Isopropylidenediphenol 80-05-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number or ID number**

ADR	3077
RID	3077
IMDG	3077
IATA	3077

14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Silver)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Silver)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Silver)
IATA	Environmentally hazardous substance, solid, n.o.s. (Silver)

14.3. Transport hazard class(es)

ADR	9
RID	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine Pollutant
IATA	Environmentally Hazardous

14.6. Special precautions for user

ADR	not applicable
-----	----------------

	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG), NZ 4.3(10) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H301 Toxic if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H341 Suspected of causing genetic defects.
H360D May damage the unborn child.
H360F May damage fertility.
H361d Suspected of damaging the unborn child.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSInfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.