

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture HumiSeal 1A27

Registration number -

UFI: QCWK-14AS-R003-6477

Synonyms None.

Product code AD0000-78

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Protective Coating for Printed Circuit Board

Uses advised against No other uses are advised.

1.3. Details of the supplier of the safety data sheet

Manufacturer/Supplier Resin Designs

Address
Resin Designs
201 Zeta Drive
Pittsburgh
Pennsylvania
15238
United States

Telephone 1-866-932-0800

E-mail Not available

Emergency telephone number +1 (703) 741-5500

EU Address HUMISEAL EUROPE SARL

Address
HumiSeal Europe SARL
4-6 Avenue Eiffel
CARRIERES SUR SEINE
Île-de-France
78420
France

Telephone +33 130098686

E-mail europetechsupport@chasecorp.cpm

Emergency telephone number Chemtrec UK: +44 (0) 870 820 0418

1.4. Emergency telephone number

General in EU	112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
National Poisons Information Centre (NVIC)	NVIC: +31 (0)88 755 8000 (Only for the purpose of informing medical personnel in cases of acute intoxications)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies. The classification of the substance or mixture has been performed in accordance with ABNT NBR 14725.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 2	H225 - Highly flammable liquid and vapour.
-------------------	------------	--

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.
--	------------	---

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Xylene, Ethylbenzene

Hazard pictograms



Signal word

Danger

Hazard statements

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P264	Wash thoroughly after handling.
P273	Avoid release to the environment.

Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
P331	Do NOT induce vomiting.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.

Storage

P403 + P235	Store in a well-ventilated place. Keep cool.
-------------	--

Disposal

Not available.

Supplemental label information

7,5 % of the mixture consists of component(s) of unknown acute dermal toxicity. 50,5 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 50,5 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Xylene	40 - < 50	1330-20-7 215-535-7	01-2119488216-32-XXXX	601-022-00-9	#
Classification: Flam. Liq. 3;H226, Acute Tox. 4;H312;(ATE: 1100 mg/kg bw), Acute Tox. 4;H332;(ATE: 11 mg/l), Skin Irrit. 2;H315, STOT SE 3;H335, STOT RE 2;H373, Asp. Tox. 1;H304					
Ethylbenzene	5 - < 10	100-41-4 202-849-4	01-2119489370-35	601-023-00-4	#
Classification: Flam. Liq. 2;H225, Acute Tox. 4;H332;(ATE: 11 mg/l), STOT RE 2;H373, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Aspiration may cause pulmonary oedema and pneumonitis. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Highly flammable liquid and vapour.

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS (Lower-tier requirements = 50 tonnes; Upper-tier requirements = 200 tonnes)

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Netherlands. OELs per Annex XIII of Working Conditions Regulation (Staatscourant no. 252, 29 December 2006), as amended

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	430 mg/m3

Netherlands. OELs per Annex XIII of Working Conditions Regulation (Staatscourant no. 252, 29 December 2006), as amended

Components	Type	Value
Xylene (CAS 1330-20-7)	TWA	97,3 ppm
		215 mg/m3
		48,6 ppm
	STEL	442 mg/m3
		100 ppm
		210 mg/m3
	TWA	47,5 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	STEL	884 mg/m3
		200 ppm
		442 mg/m3
Xylene (CAS 1330-20-7)	TWA	100 ppm
		442 mg/m3
	STEL	100 ppm
		442 mg/m3
		100 ppm
	TWA	221 mg/m3
		50 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines

Netherlands OELs (binding): Skin designation

Ethylbenzene (CAS 100-41-4)	Can be absorbed through the skin.
Xylene (CAS 1330-20-7)	Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Thermal hazards Not applicable.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.
--	--

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Colour	Clear.
Odour	Aromatic
Melting point/freezing point	-94,9 °C (-138,82 °F) estimated
Boiling point or initial boiling point and boiling range	134 °C (273,2 °F) estimated
Flammability	Highly flammable liquid
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	1,2 % estimated 0,9 %
Explosive limit – upper (%)	6,8 %
Flash point	22,9 °C (73,1 °F) estimated 15,0 °C (59,0 °F)
Auto-ignition temperature	432,22 °C (810 °F) estimated
Decomposition temperature	Not available.
pH	Does not apply.
Kinematic viscosity	Not available.
Solubility	
Solubility (water)	Negligible
Partition coefficient (n-octanol/water) (log value)	Not available.
Vapour pressure	10,69 hPa estimated
Density and/or relative density	
Density	0,96 g/cm ³ 0,86 g/cm ³ estimated
Vapour density	Not available.
Particle characteristics	Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes	No relevant additional information available.
--	---

9.2.2. Other safety characteristics

Brookfield viscosity	> 2000 - < 4000 cP
Evaporation rate	0,6 BuAc
Miscible (water)	Negligible
Specific gravity	0,96 estimated
Viscosity	> 2000 - < 4000 cP
Viscosity temperature	25 °C (77 °F)
VOC	49,5 % estimated

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms Aspiration may cause pulmonary oedema and pneumonitis. Skin irritation. May cause redness and pain.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity May be fatal if swallowed and enters airways.

Product	Species	Test Results
HumiSeal 1A27		
<u>Acute</u>		
Dermal		
LD50	Rabbit	110,2564 g/kg
Inhalation		
LC50	Mouse	10017,9482 mg/l, 6 Hours
	Rat	16282,0518 mg/l, 4 Hours
Oral		
LD50	Mouse	4076,9231 mg/kg
	Rat	7330,5513 mg/kg
Other		
LD50	Mouse	25244,4453 mg/kg
	Rat	9,7436 mg/kg

Components **Species** **Test Results**

Ethylbenzene (CAS 100-41-4)

<u>Acute</u>		
Dermal		
LD50	Rabbit	15400 mg/kg
Inhalation		
<i>Vapour</i>		
LC50	Rat	17,63 mg/l, 4 hours
Oral		
LD50	Rat	3500 mg/kg

Xylene (CAS 1330-20-7)

<u>Acute</u>		
Oral		
LD50	Rat	3523 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible.

Skin sensitisation Due to partial or complete lack of data the classification is not possible.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylbenzene (CAS 100-41-4)

2B Possibly carcinogenic to humans.

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - single exposure Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - repeated exposure Due to partial or complete lack of data the classification is not possible.

Aspiration hazard May be fatal if swallowed and enters airways.

Mixture versus substance information No information available.

11.2. Information on other hazards

Endocrine disrupting properties

The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.

Other information

Not available.

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.

Product			Species	Test Results
HumiSeal 1A27				
Aquatic				
Crustacea	EC50	Daphnia		44,5833 mg/l, 48 hours
Fish	LC50	Fish		102,8347 mg/l, 96 hours
Acute				
Crustacea	EC50	Daphnia		10,5667 mg/l, 48 hours estimated
Fish	LC50	Fish		6,2414 mg/l, 96 hours estimated
Components		Species	Test Results	
Ethylbenzene (CAS 100-41-4)				
Aquatic				
Acute				
Crustacea	EC50	Daphnia		1,8 mg/l, 48 hours
		Water flea (Daphnia magna)		1,37 - 4,4 mg/l, 48 hours
Fish	LC50	Fish		4,2 mg/l, 96 hours
Xylene (CAS 1330-20-7)				
Aquatic				
Acute				
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)		6,702 - 10,032 mg/l, 96 hours

12.2. Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient

n-octanol/water (log Kow)

Ethylbenzene (CAS 100-41-4)

3,15

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB assessment This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

12.6. Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. This mixture does not contain any substances having endocrine disrupting properties with respect to the environment as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.
12.7. Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint
14.3. Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Label(s)	3
Hazard No. (ADR)	33
Tunnel restriction code	D/E
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint
14.3. Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Label(s)	3
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint
14.3. Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Label(s)	3
14.4. Packing group	II
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1263
14.2. UN proper shipping name	PAINT
14.3. Transport hazard class(es)	
Class	3
Subsidiary hazard	-
14.4. Packing group	II
14.5. Environmental hazards	No.
ERG Code	3L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

14.1. UN number	UN1263
14.2. UN proper shipping name	PAINT
14.3. Transport hazard class(es)	
Class	3
Subsidiary hazard	-
14.4. Packing group	II
14.5. Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
14.7. Maritime transport in bulk according to IMO instruments	Not established.

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Ethylbenzene (CAS 100-41-4)

Xylene (CAS 1330-20-7)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed.

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex I, as amended

Not listed.

Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex II, as amended

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended Use of this product by young persons under the age of 18 is not allowed in accordance with the Management of Health and Safety at Work Regulations 1999 [SI 1999/3242], as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

Non-exhaustive list of substances toxic for reproduction

Xylene (CAS 1330-20-7)

Possible risk of harm to the unborn child. 2

SZW list of carcinogenic substances

Not listed.

SZW list of mutagenic substances

Not listed.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.
ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS: Chemical Abstract Service.
CEN: European Committee for Standardization.
IATA: International Air Transport Association.
IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.
IMDG: International Maritime Dangerous Goods.
MARPOL: International Convention for the Prevention of Pollution from Ships.
PBT: Persistent, bioaccumulative and toxic.
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
STEL: Short term exposure limit.
TWA: Time Weighted Average.
vPvB: Very persistent and very bioaccumulative.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

**Full text of any statements,
which are not written out in full
under sections 2 to 15**

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.

Training information

Follow training instructions when handling this material.

Disclaimer

The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only. No warranty, expressed or implied is made.