



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture HumiSeal Thinner 789

Registration number -

Synonyms HumiSeal T789, HUM T789

Product code LT0000-3567

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Protective coating thinner for printed circuit board.

Uses advised against No other uses are advised.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name CHASE CORPORATION Zeta Drive Plant

Address 201 Zeta Drive
Pittsburgh, Pennsylvania 15238
United States

Division

Telephone 1-866-932-0800

e-mail techsupport@humiseal.com

Contact person Not available.

1.4. Emergency telephone number (+1)703-527-3887 CHEMTREC

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids	Category 3	H226 - Flammable liquid and vapour.
-------------------	------------	-------------------------------------

Health hazards

Serious eye damage/eye irritation	Category 1	H318 - Causes serious eye damage.
Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
Aspiration hazard	Category 1	H304 - May be fatal if swallowed and enters airways.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.
--	------------	---

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics, n-butanol

Hazard pictograms



Signal word

Danger

Hazard statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P235	Keep cool.
P261	Avoid breathing mist/vapours.
P273	Avoid release to the environment.

Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
P331	Do NOT induce vomiting.
P310	Immediately call a POISON CENTRE/doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370 + P378	In case of fire: Use appropriate media to extinguish.
P391	Collect spillage.

Storage

P403 + P235	Store in a well-ventilated place. Keep cool.
-------------	--

Disposal

Not available.

Supplemental label information

95 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment.

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	90 - 100	64742-49-0 -	01-2119471843-32	-	Classification: Flam. Liq. 3;H226, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 3;H412
n-butanol	3 - < 5	71-36-3 200-751-6	01-2119484630-38	603-004-00-6	Classification: Flam. Liq. 3;H226, Acute Tox. 4;H302;(ATE: 500 mg/kg bw), Skin Irrit. 2;H315, Eye Dam. 1;H318, STOT SE 3;H335;H336
Butyl glycolate	< 1	7397-62-8 230-991-7	01-2119514685-36	-	Classification: Eye Dam. 1;H318, Repr. 2;H361

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.
M: M-factor
vPvB: very persistent and very bioaccumulative substance.
PBT: persistent, bioaccumulative and toxic substance.
#: This substance has been assigned Union workplace exposure limit(s).
All concentrations are in per

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
4.1. Description of first aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
Ingestion	Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
4.2. Most important symptoms and effects, both acute and delayed	Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim und

SECTION 5: Firefighting measures

General fire hazards	Flammable liquid and vapour.
5.1. Extinguishing media	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
For emergency responders	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/v
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product f
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharg
7.2. Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilat

7.3. Specific end use(s) Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle MAK-Werte

Components	Type	Value
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS 64742-49-0)	TWA	1100 mg/m3
		300 ppm
n-butanol (CAS 71-36-3)	STEL	310 mg/m3
		100 ppm
	TWA	310 mg/m3
		100 ppm

Biological limit values

Switzerland. SUVA Grenzwerte am Arbeitsplatz: Aktuelle BAT-Werte

Components	Value	Determinant	Specimen
n-butanol (CAS 71-36-3)	2 mg/g	n-Butanol	Creatinine in urine
	10 mg/g	n-Butanol	Creatinine in urine

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls

Appropriate engineering controls Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airb

Individual protection measures, such as personal protective equipment

General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Chemical respirator with organic vapour cartridge and full facepiece.
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves.

- Other	Wear suitable protective clothing.
Respiratory protection	Chemical respirator with organic vapour cartridge and full facepiece.
Thermal hazards	Not applicable.
Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, f

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Liquid.
Colour	Colourless.
Odour	Not available.
Melting point/freezing point	Not available.
Boiling point or initial boiling point and boiling range	143 °C (289,4 °F) estimated
Flammability	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit – upper (%)	Not available.
Flash point	24,0 °C (75,2 °F)
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
pH	Not available.
Kinematic viscosity	Not available.
Solubility	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water) (log value)	Not available.
Vapour pressure	Not available.
Density and/or relative density	
Density	0,75 g/cm³
Vapour density	Not available.
Particle characteristics	Not available.

9.2. Other information

9.2.1. Information with regard to physical hazard classes No relevant additional information available.

9.2.2. Other safety characteristics

VOC 4,01 % estimated

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.
---------------------	--

Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye damage.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Symptoms	Aspiration may cause pulmonary oedema and pneumonitis. May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity May be fatal if swallowed and enters airways.

Product	Species	Test Results
HumiSeal Thinner 789		
Acute		
Dermal		
LD50	Rabbit	84788 mg/kg
Inhalation		
LC50	Rat	64 mg/l, 4 Hours
Oral		
LD50	Rat	19701 mg/kg
Components	Species	Test Results

Butyl glycolate (CAS 7397-62-8)

Acute		
Inhalation		
<i>Mist</i>		
LC50	Rat	> 6,2 mg/l, 4 hours
Oral		
LD50	Rat	4240 mg/kg

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS 64742-49-0)

Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg > 5 mg/kg
Inhalation		
<i>Vapour</i>		
LC50	Rat	> 4,96 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg > 4800 mg/kg

Skin corrosion/irritation	Due to partial or complete lack of data the classification is not possible.
Serious eye damage/eye irritation	Causes serious eye damage.
Respiratory sensitisation	Due to partial or complete lack of data the classification is not possible.
Skin sensitisation	Due to partial or complete lack of data the classification is not possible.
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.
Carcinogenicity	Due to partial or complete lack of data the classification is not possible.
Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - single exposure	May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure	Due to partial or complete lack of data the classification is not possible.
Aspiration hazard	May be fatal if swallowed and enters airways.
Mixture versus substance information	No information available.

11.2. Information on other hazards	
Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. This mixture does not contain any substances having endocrine disrupting properties with respect to human health as assessed in accordance with the criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605, at a concentration equal to or greater than 0.1% by weight.
Other information	Not available.

SECTION 12: Ecological information

12.1. Toxicity	Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are not met for hazardous to the aquatic environment, acute hazard.
-----------------------	---

Product			Species	Test Results
HumiSeal Thinner 789				
Aquatic				
Crustacea	EC50	Daphnia	3,947 mg/l, 48 hours	
Fish	LC50	Fish	9,4716 mg/l, 96 hours	
Acute				
Crustacea	EC50	Daphnia	23,0936 mg/l, 48 hours estimated	
Fish	LC50	Fish	10,4352 mg/l, 96 hours estimated	
Components			Species	Test Results

Butyl glycolate (CAS 7397-62-8)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia	> 100 mg/l, 48 hours
Fish	LC50	Fish	23,1 mg/l, 96 hours

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS 64742-49-0)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Daphnia	> 22 - < 46 mg/l, 48 hours
		Water flea (Daphnia pulex)	2,7 - 5,1 mg/l, 48 hours
	LC50	Fish	> 10 - < 30 mg/l, 96 hours
		Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8,8 mg/l, 96 hours
			8,8 mg/l, 96 hours

n-butanol (CAS 71-36-3)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	1897 - 2072 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	100 - 500 mg/l, 96 hours

12.2. Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.
--	--

12.3. Bioaccumulative potential

Partition coefficient	
n-octanol/water (log Kow)	
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS 64742-49-0)	4 - 5,7
n-butanol (CAS 71-36-3)	0,88

Bioconcentration factor (BCF)	Not available.
--------------------------------------	----------------

12.4. Mobility in soil	No data available.
-------------------------------	--------------------

12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.
---	---

12.6. Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. This mixture does not contain any subs
--	---

12.7. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.
------------------------------------	---

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1263
14.2. UN proper shipping name	PAINT RELATED MATERIAL
14.3. Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Label(s)	3
Hazard No. (ADR)	30
Tunnel restriction code	D/E
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN1263
14.2. UN proper shipping name	PAINT RELATED MATERIAL
14.3. Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Label(s)	3
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN1263
14.2. UN proper shipping name	PAINT RELATED MATERIAL
14.3. Transport hazard class(es)	
Class	3
Subsidiary hazard	-
Label(s)	3
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number	UN1263
14.2. UN proper shipping name	Paint related material
14.3. Transport hazard class(es)	
Class	3
Subsidiary hazard	-
14.4. Packing group	III
14.5. Environmental hazards	No.
ERG Code	3L
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

14.1. UN number	UN1263
14.2. UN proper shipping name	PAINT RELATED MATERIAL
14.3. Transport hazard class(es)	
Class	3
Subsidiary hazard	-
14.4. Packing group	III
14.5. Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
14.7. Maritime transport in bulk according to IMO instruments	Not established.

ADN; ADR; IATA; IMDG; RID

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations**

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**
Not listed.
- Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended**
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**
Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**
Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**
Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**
Not listed.

Authorisations

- Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**
Not listed.

Restrictions on use

- Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended**
- **Conditions of restriction given for the associated entry number should be considered**
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS 64742-49-0)
- Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics (CAS 64742-49-0)
- Regulation 2019/1148 on Marketing and Use of Explosive Precursors, Annex I, as amended**
Not listed.

Not listed.

Other EU regulations	Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended ANNEX 1, PART 1 Categories of dangerous substances Hazard categories in accordance with Regulation (EC) No 1272/2008 - P5a, b or c FLAMMABLE LIQUIDS - E2 Hazardous
Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

Switzerland. Schedules 1A-3B on Substances Subject to ChKV, Regulation on the Control of Chemicals with Civilian and Military Use (ChKV)

Not listed.

15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out. All components of the mixture are on the EINECS or ELINCS inventories.
---	---

SECTION 16: Other information

List of abbreviations	ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways. ADR: Agreement concerning the International Carriage of Dangerous Goods by Road. CAS: Chemical Abstract Service. CEN: European Committee for Standardization. IATA: International Air Transport Association. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG: International Maritime Dangerous Goods. MARPOL: International Convention for the Prevention of Pollution from Ships. PBT: Persistent, bioaccumulative and toxic. RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short term exposure limit. TWA: Time Weighted Average. vPvB: Very persistent and very bioaccumulative.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any statements, which are not written out in full under sections 2 to 15	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H412 Harmful to aquatic life with long lasting effects.
Revision information	This document has undergone significant changes and should be reviewed in its entirety.
Training information	Follow training instructions when handling this material.
Disclaimer	The information offered in this data sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its